

Appl. No. 09/917,522

In the Claims

1. (currently amended) A method, comprising:  
detecting whether a floppy disk operation is a write;  
and,  
5       masking DMA requests from at least one DMA channel during  
said write thereby preventing data corruption, wherein said at  
least one DMA channel has a higher priority than a DMA channel  
associated with said floppy disk operation.
- 10   2. (original) The method of claim 1, wherein said masking  
DMA requests is only during a portion of said write.
3. (original) The method of claim 1, wherein said masking  
DMA requests is during all of said write.
- 15   4. (original) The method of claim 1, wherein said detecting  
and said masking is accomplished by said floppy disk driver  
routine.
5. (cancelled)
6. (original) The method of claim 1, comprising:  
providing a timer interrupt service routine that accomplishes  
said masking.
- 20   7. (original) The method of claim 6, comprising:  
reprogramming a timer to interrupt at a more rapid rate.
8. (original) The method of claim 6, comprising:  
reading a DMA byte count.
9. (original) The method of claim 8, comprising:

Appl. No. 09/917,522

accomplishing said masking after said DMA byte count reaches a threshold.

10. (original) The method of claim 8, comprising:  
estimating when said write will complete from said DMA  
5 byte count.

11. (original) The method of claim 10, wherein said estimating includes a linear interpolation.

12. (original) The method of claim 10, wherein said estimating includes a least squares fit method.

10 13. (original) The method of claim 10, wherein said estimating includes a polynomial fit method.

14. (original) The method of claim 10, comprising:  
determining a time to accomplish said masking based upon  
a result of said step of estimating.

15 15. (currently amended) An apparatus, comprising:  
a floppy disk controller receiving data via DMA accesses  
under the control of a DMA controller wherein said DMA  
controller ignores at least one DMA request line when an  
underrun error may occur, wherein said at least one DMA  
20 request line has a higher priority than a DMA request line  
associated with said floppy disk controller.

16. (original) The apparatus of claim 15 wherein said DMA controller ignores said at least one DMA request line for a transfer of data comprising a whole sector.

25 17. (original) The apparatus of claim 15 wherein said DMA

Appl. No. 09/917,522

controller ignores said at least one DMA request line for a transfer of data comprising less than a whole sector.

18. (original) The apparatus of claim 15 wherein said DMA controller ignores said at least one DMA request line after a threshold number of bytes have been transferred.

19. (original) The apparatus of claim 15 wherein said DMA controller ignores said at least one DMA request line after a first time period has elapsed.

20. (original) The apparatus of claim 15 wherein said DMA controller ignores said at least one DMA request line a second time period before a transfer of a last byte.

21. (original) The apparatus of claim 20 wherein said second time period is based upon an estimate of when said transfer of said last byte will occur.

22. (original) The apparatus of claim 21 wherein said estimate is derived by monitoring a DMA byte count.

23. (original) The apparatus of claim 21 wherein said estimate is derived by monitoring a system clock.

24. (original) The apparatus of claim 21 wherein said estimate is based upon samples taken of a DMA byte count and a system clock.

25. (original) The apparatus of claim 24 wherein said samples are interpolated linearly to produce said estimate.

26. (original) The apparatus of claim 24 wherein said

Appl. No. 09/917,522

samples are input to a least squares fit process to produce said estimate.

27. (original) The apparatus of claim 24 wherein said samples are input to a polynomial curve fitting process to produce said estimate.

28. (previously amended) An apparatus, comprising:  
a DMA controller in communication with a floppy disk controller; and,

means for masking at least one DMA request line when a DMA underrun may occur due to an improperly designed floppy disk controller, wherein said at least one DMA request line has a higher priority than a DMA request line associated with said floppy disk controller.

29. (original) The apparatus of claim 28 wherein said at least one DMA request line is masked based upon an estimate generated by a means for estimating.

30. (original) The apparatus of claim 29 wherein said means for estimating includes means for linear interpolation.

31. (original) The apparatus of claim 29 wherein said means for estimating includes means for performing a least squares fit analysis.

32. (original) The apparatus of claim 29 wherein said means for estimating includes means for performing a polynomial fit analysis.

33. (currently amended) A program storage medium readable by a computer, tangibly embodying a program of instructions

Appl. No. 09/917,522

executable by a computer to perform method steps, said method steps comprising:

5 detecting whether a floppy disk operation is a write;  
and, masking DMA requests from at least one DMA channel during  
said write thereby preventing data corruption, wherein said at  
least one DMA channel has a higher priority than a DMA channel  
associated with said floppy disk operation.

10 34. (original) The program storage medium of claim 33,  
wherein said masking DMA requests is only during a portion of  
said write.

35. (original) The program storage medium of claim 33,  
wherein said masking DMA requests is during all of said write.

15 36. (original) The program storage medium of claim 33,  
wherein said detecting and said masking is accomplished by  
said floppy disk driver routine.

37. (cancelled)

38. (original) The program storage medium of claim 33,  
comprising:

20 providing a timer interrupt service routine that  
accomplishes said masking.

39. (original) The program storage medium of claim 38,  
comprising:  
reprogramming a timer to interrupt at a more rapid rate.

25 40. (original) The program storage medium of claim 38,  
comprising: reading a DMA byte count.

Appl. No. 09/917,522

41. (original) The program storage medium of claim 40,  
comprising:

accomplishing said masking after said DMA byte count  
reaches a threshold.

5 42. (original) The program storage medium of claim 40,  
comprising:

estimating when said write will complete from said DMA  
byte count.

10 43. (original) The program storage medium of claim 42,  
wherein said estimating includes a linear interpolation.

44. (original) The program storage medium of claim 42,  
wherein said estimating includes a least squares fit method.

45. (original) The program storage medium of claim 42,  
wherein said estimating includes a polynomial fit method.

15 46. (original) The program storage medium of claim 42,  
comprising:

determining a time to accomplish said masking based upon  
a result of said step of estimating.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**